dynamometers and inclinometers

- advanced digital technology for muscle strength, range-of-motion measurements and ergonomic applications including job task analysis and functional capacity testing
- units are bluetooth enabled to deliver information directly from the unit to your computer for use with optional data or clinical software packages
- results are displayed on the unit in an LCD display
- strength measurements can be shown in lb, kg or newtons and can be set to a high (3 lb) or low (0.8 lb) threshold setting.
- strength measurements and range-of-motion units are accurate to within 1º
- automatic shut-off prolongs battery life
- units come with a carrying case, instruction manual, test result forms, batteries and a 1 year warranty

MicroFET 2[™] MMT

- displays peak force and time duration
- versatile push attachments ensure proper muscle isolation for increased testing validity
- 300 lb capacity

evaluation

includes: 3 push attachments, test forms, wall chart, case, 2 3.7V lithium batteries, AC adapter and battery charger

12-0381W	MF2, wireless	1,095.00
12-0381WC	MF2, with clinical software	1,595.00
12-0381WD	MF2, with data collection software	1,595.00
12-0381WCD	MF2, with both software packages	2,095.00


MicroFET 5[™] single inclinometer

- uses simple keypad prompts to calculate and display spinal segment ROM results
- pre-programmed protocols for cervical, thoracic and lumbar ROM test
- unit can perform extremity ROM tests
- does not support external software (data or clinical)
- unit contains: test forms, wall chart, case and 9V battery

12-0299W MF5 1.095.00



icro



Software

12-0279 data software 500.00 12-0278 clinical software 500.00

- MicroFET 3[™] MMT/ inclinometer
- manual muscle tester and inclinometer in one unit

and HandGRIP

provides fast, accurate and reliable digital results for MMT and ROM testing



- ROM measurements require single unit only
- 150 lb force capacity
- includes: 3 push attachments, test forms, wall chart, case, 3.7V lithium ion battery and AC adapter

12-0382W	MF3, wireless	1,395.00
12-0382WC	MF3, with clinical software	1,895.00

MicroFET 6[™] dual inclinometer

- can be used as a single or dual site inclinometer
- measures in 1° increments from 0° to +/- 180°
- use with either AMA or DRE protocols
- unit contains: test forms, wall chart, case and 3.7V rechargeable lithium ion battery
- 1,095.00 12-0289W MF6, wireless 12-0289WC MF6, with clinical software 1.595.00

MicroFET™

statistics are collected and narrative and graphic reports can be

microFET2, microFET3, microFET4, and microFET6, HandGRIP

FEI Retail, PO Box 1076, White Plains, New York 10602 USA tel: 888-211-5242 + 914-407-0150 orders@FEIretail.com fax: 888-211-5765 + 914-407-0151